## \$FLIR



## OUTDOOR THERMAL MONOCULAR

FLIR SCION® OTM

The FLIR Scion<sup>®</sup> OTM captures clear thermal imaging and leverages an easy-to-use interface to quickly detect objects of interest in complete darkness and through glaring light or haze. Built around FLIR's powerful Boson<sup>®</sup> core, the Scion OTM produces 9 Hz thermal imaging and records geotagged video and still images for playback long after the day is done. A rugged, IP67-rated housing and intuitive controls allow single-hand operation in harsh weather conditions, maintaining reliable thermal imaging in the most demanding outdoor environments.

www.flir.com



VERSATILE LENS OPTIONS Available long-range lenses for the Scion family of thermal monoculars offers a new level of clarity and reach.

High-performance thermal lenses ranging from 13.8-36 mm offer a choice between quick, closeproximity detection and fine-tuned, long-range observation. When your adventure demands reliable vision from a distance, premium Scion lenses can detect targets up to 1420 m away. 25 mm and 36 mm Scion optics leverage a manual focus ring to achieve a new level of clarity among FLIR thermal monoculars.



TRUSTED THERMAL DETECTION Powered by the breakthrough FLIR Boson thermal core.

Able to perform at any time of day, thermal imaging sees through complete darkness, glaring light, and lingering haze to provide superior awareness in difficult conditions. The advanced image processing of the FLIR Boson thermal core and a vivid high definition display offer superb clarity in a 9 Hz thermal image.

ONBOARD VIDEO AND IMAGE RECORDING Revisit every wildlife encounter in sharp thermal imaging.


The Scion OTM is ready to capture any wildlife encounter with onboard video and image recording. Internal storage and a built-in microSD<sup>M</sup> card slot provide enough memory for the most demanding trips, while Bluetooth<sup>®</sup> and Wi-Fi capability allow simple file transfer between devices.

## SPECIFICATIONS

General	Scion OTM130	Scion OTM230	Scion OTM260	Scion OTM430			
Core Technology	BOSON 12 µm VOx Microbolometer						
Detector Resolution	320 ×	0 × 256 640 × 512		320 × 256			
Refresh Rate		9 Hz					
Lens System	13.8 mm	18 mm		36 mm			
Field of View (H × W)	16° × 12°	12° × 9°	24° × 18°	6° × 4.5°			
Optical Magnification	1.5x	1.9x	1x	3.8x			
Digital Zoom	1X   2>	(   4X   1X   2X   4X   8X		1X 2X 4X			
Video Recording	Yes						
Image Capturing	Yes						
Internal Memory	2 GB Internal Storage / Optional microSD <sup>™</sup> Card (up to 128 GB)						
Focusing Range		manual					
Eye Relief	16 mm						
Display	Quad-VGA (1280x960) High definition display						
Display Focus	Manual						
Features	atures						
Color Palettes	White Hot; Black Hot; Iron Bow; Rainbow; Graded Fire; Lava						
Viewing Modes	Scouting, Picture-in-Picture , Lock Span Mode						
GPS	No Yes						
Advanced media capture	Yes						
Media capturing	2 GB Internal storage / Optional micro SD™card (up to 128 GB)						
Date/Time Stamp	Yes						
Auto Power OFF	Yes						
Magnetic Compass	Yes						
Accelerometer	Yes						
Interfacing							
USB Type	USB-C; Power In; Video Out; Video and Image File Transfer						
Power							
Battery Type / Life	6x CR123A 3V Lithium Battery / Up to 4.5 Hours at 20°C or Rechargeable battery pack / Up to 10 Hours at 20°C						

	Scion OTM130	Scion OTM230	Scion OTM260	Scion OTM430			
Communications							
Bluetooth™	BLE 4.1+						
Wi-Fi	Video Streaming						
Physical							
size	227 x 77 x 61 mm (9x3x2.4 in)			239 x 77 x 73 mm (9.4 x 3 x 2.4 in)			
Weight	Without Batteries: 452 g; WithBatteries 572 g			Without Batteries: 580 g; With Batteries 794 g			
Environmental rating	IP67 waterproof / 2m drop						
Operating Temp.	-20°c to 50°c						
Storage Temp.	-40°c to 70°c						
Color (Housing)	Gray / Black						
Mounting	1/4-20 Tripod Mount / Optional docking station						
Country of Origin	USA						
Included in Box	SCION, Battery tray, 6xCR123, USB-C cable, Black MOLLE pouch, Quick Start Guide						





400 series units



Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com

For Detailed Information

Email: info@irmarinetech.com

WebSite: www.irmarinetech.com

Phone: 0216 755 00 16



IRMARINETECH Yazılım Danışmanlık

## DETECTION RANGE PERFORMANCE



Ranges calculated using Johnson criteria (1.8 m man)

