

## LRAD<sup>®</sup> 100X MAG-HS Long Range Communication – High Strength Mag Mount



#### **PRODUCT INFORMATION**

LRAD-100X-BLK-MAG-HS

LRAD 100X MAG-HS system includes magnetic base with 600 lbs. of holding and 120 lbs. of shear force\*, and accompanying mounting yoke to secure the LRAD to metallic surfaces including vehicle roofs

#### **INCLUDED ACCESSORIES**

| MP3 Player            | MP3 player records/plays up to 2GB of messages and tones           |
|-----------------------|--|
| Record on the Fly Mic | Microphone with record and playback feature for immediate playback |
| MP3 Auxiliary Cable   | Allows connection to any audio device with a headphone jack        |
| USB Cable             | USB cable for downloading files to the MP3 player                  |
| Li-Fe-PO4 Battery     | 8-Hour Lithium Iron Phosphate rechargeable battery                 |
| Battery Charger       | AC powered battery charger with LED battery charge status display  |
| Hard Case             | Watertight, dust proof, rugged enclosure for storage and transport |

#### **OPTIONAL ACCESSORIES**

| HD Action Camera       | During LRAD operation, record High Definition, date/time stamped video and audio with this compact, rugged digital camera |
|------------------------|---|
| AC Power Supply        | Can be powered by a standard AC source in place of the battery  |
| Stud Mount             | Mounting yoke kit for LRAD-100X, compatible for LRAD tripods (tripod not included)  |
| Stud Kit               | Weldment Stud Kit   |
| Medium-Duty Tripod Kit | Includes reusable hard case   |
| Table Mount Kit        | Fixed mount for flat surfaces   |
| Tactical Pack          | Rugged backpack for operation of the LRAD 100X within the pack or on the move   |
| Front Carry Pack       | For mobile or stationary operation of the LRAD 100X   |

#### DIRECTIONALITY, POWER & RANGE

- Powerful, intelligible voice communications up to 600 meters
- Focused, directional broadcasts for targeted communication
- Safely communicate beyond standoff distances
- Create instant acoustic standoff perimeter
- Deliver clearly heard and understood communications into buildings & vehicles

#### **FEATURES**

- > 8-hour rechargeable battery
- Operate easily with gloves or MOPP gear
- Optional power sources
- > Simple operator interface
- > Water resistant
- > HD Camera (optional) Quick connect/disconnect camera and mount for recording video and audio during LRAD operation. Includes 4GB micro SDHC for up to 210 minutes of date and time stamped recordings

#### **MARKETS SERVED**

- > Law Enforcement
- > Defense
- > Commercial Security
- > Critical Infrastructure Security
- > Maritime
- > Homeland Security
- Fire Rescue & Incident Management
- › Port & Border Security
- > Emergency Warning
- Mass Communication
- › Wildlife Preservation & Control

\*Combined force and shear ratings of mag mount for 14" unfinished steel. Painted surfaces and thinner metals will have less holding and shear force.



#### SELF-CONTAINED, PORTABLE COMMUNICATION KIT

The LRAD 100X MAG-HS Kit consists of an LRAD 100X, a mount with four high strength magnets that clamp to, and unclamp from, magnetic surfaces with a turn of a knob, an LRAD Wireless Kit for remote operation, an AC-powered battery charger, an MP3 player with an all-weather record-on-the-fly mic, a watertight, dust proof hard case, and other accessories.

With unparalleled vocal clarity and up to 30db louder than bullhorns, megaphones, and vehicle P.A. systems, the LRAD 100X is also four to six times louder than other acoustic hailers of comparable size and weight. LRAD's optimized driver and waveguide technology ensures every message is clearly broadcast, heard and understood, even above engine, crowd, siren, and background noise.

The LRAD warning tone commands attention to the voice messages that follow and provides a safer alternative to non-lethal and kinetic measures for changing behavior.



# LRAD<sup>®</sup> 100X MAG-HS

Long Range Communication – High Strength Mag Mount

#### **ACOUSTIC PERFORMANCE**

| Maximum Peak Output       | 140dB SPL @ 1 meter, C-weighted   |
|---------------------------|---|
| Maximum Continuous Output | 137db SPL@1 meter, A-weighted   |
| Sound Projection          | +/- 15° @ 1kHz/-3dB   |
| Communication Ranges      | Maximum range up to 600 meters in ideal conditions. Operational range up to 250 meters over 88dB<br>of background noise. Ranges based on continuous output. |

#### **ENVIRONMENTAL PERFORMANCE<sup>1</sup>**

| Hot Operating Temperature  | MIL-STD-810G, Method 501.5, Procedure II, Design type Hot, 60°C         |  |
|----------------------------|---|--|
| Cold Operating Temperature | MIL-STD-810G, Method 502.5, Procedure II, Design type Basic Cold, -33°C |  |
| Hot Storage Temperature    | MIL-STD-810G, Method 501.5, Procedure I, 70°C                           |  |
| Cold Storage Temperature   | MIL-STD-810G, Method 502.5, Procedure I, -40°C                          |  |
| Operating Humidity         | MIL-STD 810G, Method 507.5, Procedure II – Aggravated Cycle             |  |
| Rain                       | MIL-STD-810G, Method 506.5, Procedure I, Blowing rain                   |  |
| Salt Fog                   | MIL-STD-810G, Method 509.5  |  |
| Shipboard Vibration        | MIL-STD-167-1A  |  |
| Shipboard Shock            | MIL-S-901D, Class I, Shock grade B                                      |  |
| Random Vibration           | MIL-STD-810G, Method 516.6, Procedure I, (Functional shock)             |  |
|                            |   |  |

<sup>1</sup>TESTED BY NATIONAL TECHNICAL SYSTEMS (NTS) FOLLOWING MIL-STD-810G, MIL-STD-167-1A & MIL-S-901D.

#### **MECHANICAL**

| Dimensions   | 17"W x 21"H x 9"D (43 x 53x 23 cm)                        |
|--------------|---|
| Weight       | 22 lbs.(10 kg) with battery, accessories and cables       |
| Construction | Injection molded, impact resistant polymer, 6061 Aluminum |

#### **ELECTRICAL REQUIREMENTS<sup>2</sup>**

| Power Consumption                              | Typical Power consumption 85 Watts (With tone)<br>Normal power consumption 20 Watts (With voice content)  |
|--|---|
| Power Input                                    | 10.8 to 16.8 VDC, Included rechargeable 13.2 VDC Li-Fe-PO battery for up to 2 hours of continuous operation at maximum volume on a full charge. |
| <sup>2</sup> BATTERY LIFE UP TO 2 HOURS OF CON | ITINUOUS OPERATION AT MAXIMUM TONE ON A FULL CHARGE. ADAPTERS AVAILABLE FOR AUTO CIGARETTE LIGHTER  |

BATTERY LIFE UP TO 2 HOURS OF CONTINUOUS OPERATION AT MAXIMUM TONE ON A FULL CHARGE. ADAPTERS AVAILABLE FOR AUTO CIGARETTE LIGHTER AND FOR 2590 RECHARGEABLE MILITARY BATTERY.

#### SAFETY<sup>3</sup>

MIL-STD-1474D

<sup>3</sup>MIL-STD-1474D STANDARD ESTABLISHES ACOUSTICAL NOISE LIMITS AND PRESCRIBES TESTING REQUIREMENTS AND MEASUREMENT TECHNIQUES FOR DETERMINING CONFORMANCE TO THE NOISE LIMITS SPECIFIED THEREIN.

#### ELECTROMAGNETIC COMPATIBILITY (EMC)<sup>4</sup>

FCC Part 15 class A radiated emissions, CE

<sup>4</sup>REQUIREMENTS FOR THE CONTROL OF ELECTROMAGNETIC INTERFERENCE CHARACTERISTICS OF SUBSYSTEMS AND EQUIPMENT.

#### Genasys - A Critical Communications Company

Genasys Inc. is the global leader in Long Range Voice Broadcast systems and advanced Public Safety Notification and Emergency Warning solutions. The Company's LRAD systems are in service in 72 countries and in more than 450 U.S. cities, counties, and states In diverse applications, including public safety mass notification, law enforcement defense, border and homeland security, critical infrastructure protection, fire rescue and emergency management, maritime and port security, and wildlife control and preservation.

For more information, please visit: genasys.com



(f

🏠 NTS



LRAD products are available for purchase through multiple channels including: GSA Advantage, Federal and State grants, FEMA RKB Standardized Equipment List (SEL), and others. More information: sales@genasys.com

### genasys.com

TEL: 858-676-1112 | +1 855 GENASYS | SALES@GENASYS.COM 16262 WEST BERNARDO DRIVE · SAN DIEGO, CA 92127 USA SPECIFICATIONS SUBJECT TO CHANGE · ©2020 GENASYS INC. 18110